

## **Geotechnical Data Report**

Proposed Convention Center Completion Project  
Spokane, Washington

*for*

**Spokane Public Facilities District**

January 15, 2013



## **Geotechnical Data Report**

Proposed Convention Center Completion Project  
Spokane, Washington

*for*

**Spokane Public Facilities District**

January 15, 2013



523 East Second Avenue  
Spokane, Washington 99202  
509.363.3125

**Geotechnical Data Report**  
**Proposed Convention Center Completion**  
**Project**  
**Spokane, Washington**

**File No. 12088-001-06**

**January 15, 2013**

Prepared for:

Spokane Public Facilities District  
West 720 Mallon Avenue  
Spokane, Washington 99201

Attention: Kevin Twohig, CFE  
Executive Director

Prepared by:

GeoEngineers, Inc.  
523 East Second Avenue  
Spokane, Washington 99202  
509.363.3125



*Teresa A. Dugger*

Teresa A Dugger, PE  
Geotechnical Engineer

*James B. Harakas*

James B. Harakas, PE, LEG  
Senior Principal

TAD:JBH:tlm

cc: Hill International, Inc., Matt Walker, AIA, Project Manager

Disclaimer: Any electronic form, facsimile or hard copy of the original document (email, text, table, and/or figure), if provided, and any attachments are only a copy of the original document. The original document is stored by GeoEngineers, Inc. and will serve as the official document of record.

Copyright© 2013 by GeoEngineers, Inc. All rights reserved.

# Table of Contents

<b>INTRODUCTION .....</b>	<b>1</b>
<b>SCOPE OF SERVICES .....</b>	<b>1</b>
<b>SITE CONDITIONS.....</b>	<b>1</b>
Surface Conditions.....	1
Literature Review .....	1
General .....	1
Geologic Literature Review.....	2
Subsurface Conditions .....	2
Laboratory Testing .....	2
<b>LIMITATIONS .....</b>	<b>3</b>
<b>REFERENCES .....</b>	<b>3</b>

## LIST OF TABLES

Table 1. Summary of Previous Geotechnical Studies

## LIST OF FIGURES

Figure 1. Vicinity Map

Figure 2. Site Plan

## APPENDICES

Appendix A. Existing Exploration Logs

Appendix B. Auqila GeoSciences, Inc. – Seismic Refraction Survey

Appendix C. Report Limitations and Guidelines for Use

## INTRODUCTION

This report presents the results of our geotechnical data compilation for the proposed Convention Center Completion (CCC) project in Spokane, Washington. We understand this data report will be used during development of design/build plans for the proposed CCC. The approximate location of the proposed project is shown on the Vicinity Map, Figure 1.

The proposed CCC site, along with the adjacent Convention Center Exhibit Hall (CCE site), was the subject of previous geotechnical and environmental site assessment (ESA) studies by GeoEngineers (GeoEngineers, 2002, 2004, 2005). We understand the SPFD plans to redevelop the proposed CCC site to expand the existing Exhibit Hall with additional convention center space. Redevelopment of the CCC site will include, at a minimum: demolition of the former C.I. Shenanigan's (Shenanigan's) restaurant building; demolition of existing asphalt concrete and portland cement concrete pavements; relocation of existing underground utilities; earthwork to establish proposed grades; installing new underground utilities; and constructing the proposed CCC building. New landscaping also will be part of site improvements.

## SCOPE OF SERVICES

The purpose of our geotechnical data report was to provide a summary of geotechnical data previously developed by GeoEngineers for the existing CCE project. Our current geotechnical services were provided in general accordance with our agreement with the Spokane Public Facilities District, dated October 31, 2012 and included:

1. Review and compilation of previous geotechnical and environmental evaluations in our files for the existing CCE. We also reviewed the geologic literature and soil survey for information regarding subsurface soil, rock and groundwater conditions in the vicinity of the proposed CCE site.

## SITE CONDITIONS

### Surface Conditions

The site of the proposed CCC is located north of Spokane Falls Boulevard, south of the Spokane River, between Spokane Falls Court and Division Street, on the east end of Spokane's central business district and downtown area. The central and east portions of the site are occupied by the former Shenanigan's building and parking lot. Access drives for the Double Tree Hotel, and walkways and landscaping extend through the west portion of the subject site. Site grades are relatively level, ranging generally from about Elevation 1,877 on the north to Elevation 1,881 near the southeast and southwest corners of the site. (Elevations in the text of this report refer to NAVD 88 datum.)

### Literature Review

#### **General**

As part of our effort for this geotechnical data report, we completed a records review of: Washington State Department of Natural Resources (DNR) geologic maps; in-house geotechnical

and environmental reports; and geotechnical and environmental reports previously provided to us by the City of Spokane. The purpose of this effort was to identify existing data for the adjacent CCE site to the south and the proposed CCC site.

### **Geologic Literature Review**

Geologic mapping completed by Derkey, Hamilton and Stradling indicates that a significant portion of the downtown district is located within the Columbia Basin also known as the Columbia Plateau. This is a broad physiogeographic area in eastern Washington, southwestern Idaho and northern Oregon that was covered with lava from extensive volcanic events that occurred during the Miocene age (13 to 16 million years ago). The lava created a layered basalt formation known as the Columbia River Basalt Group with interbeds of fine-grained soils. This unit, which covers approximately 36 percent of Washington State, was derived from four major volcanic events. The formation reaches a maximum thickness on the order of about 16,000 feet. The basalt typically consists of dark gray, fine-grained rock.

The Spokane downtown area, including the CCC site, retains little of its original geologic surface characteristics because of past and present development. To develop relatively level sites, it was common practice during Spokane's early history to level rock outcrops and fill low areas with rock rubble, local gravelly soils or debris. Geotechnical reports from the area also indicate the presence of ash, melted glass, brick, metal and other deleterious debris that probably originated from the Spokane fire of 1889.

### **Subsurface Conditions**

We evaluated possible subsurface conditions beneath the project area by reviewing in-house geotechnical, environmental and geophysical reports. The approximate locations of explorations on the existing CCE site and proposed CCC site are presented on the Site Plan, Figure 2. A summary of subsurface soil and groundwater conditions is provided in Summary of Previous Geotechnical Studies, Table 1. Exploration logs are provided in Appendix A. A geophysical survey completed for the existing CCE site is contained in Appendix B.

Perched groundwater was encountered in some of the explorations beneath the existing CCE and proposed CCC site, at variable depths, but generally near the contact between overlying fill or natural soil deposits, and underlying basalt rock. The depth to groundwater will vary seasonally and could be higher than reported at the time of completion of the previous explorations. Depth to groundwater also might be influenced by the water level in the Spokane River in those portions of the site where rock depth below ground surface increases, generally on the north side of the property.

### **Laboratory Testing**

Samples acquired during GeoEngineers' geotechnical exploration activities were returned to our laboratory for evaluation and testing of select samples. Because of potential contamination, testing was limited to a few samples. Results of testing are included on the boring logs.

Select samples obtained during environmental assessment evaluations by GeoEngineers were submitted for analytical testing for select analytes. Results of that testing will be presented in the

Corrective Action Plan for the proposed Convention Center Completion project, which will be submitted under separate cover.

## LIMITATIONS

We have prepared this data report for Spokane Public Facilities District for the proposed Convention Center Completion Project in Spokane, Washington. The Spokane Public Facilities District may distribute copies of this report to authorized agents, regulatory agencies and design/build teams as may be required for the project.

Within the limitations of scope, schedule and budget, our services have been executed in accordance with generally accepted practices for geotechnical engineering in this area at the time this report was prepared. No other warranty, express or implied, is made.

Any electronic form, facsimile or hard copy of the original document (email, text, table, and/or figure), if provided, and any attachments should be considered a copy of the original document. The original document is stored by GeoEngineers, Inc. and will serve as the official document of record.

Please refer to Appendix C titled "Report Limitations and Guidelines for Use" for additional information pertaining to use of this report.

## REFERENCES

Derkey, Robert E., Hamilton, Michael M., and Stradling, Dale F., "Geologic Map of the Spokane Northwest 7.5-minute Quadrangle, Spokane County, Washington" Washington State Division of Geology and Earth Resources, Open File Report 2004-3.

GeoEngineers, Inc., "Geotechnical Consultation during Design of Promenade Drilled Shaft Foundations, Proposed Convention Center Expansion, Spokane, Washington," Project No. 0110-047-07, September 13, 2005.

GeoEngineers, Inc., "Supplemental Geotechnical Engineering Study, Proposed Convention Center Expansion Project, Spokane, Washington," Project No. 0110-047-02, May 13, 2004.

GeoEngineers, Inc., "Geotechnical Engineering Study, Centennial Trail, Convention Center Expansion, Spokane, Washington," Project No. 0110-047-04, January 8, 2004.

GeoEngineers, Inc., "Limited Phase I and Phase II Environmental Site Assessment, Proposed Convention Center Expansion Option 2 Site, Spokane, Washington," Project No. 0110-047-00, September 26, 2002.

GeoEngineers, Inc., "Geotechnical Engineering Study, Proposed Convention Center Expansion Option 2 Site, Spokane, Washington," Project No. 0110-047-00, September 25, 2002.



**Table 1**  
**Summary of Previous Geotechnical Studies**  
**Proposed Convention Center Expansion**  
**Spokane, Washington**

<b>Consultant</b>	<b>Exploration Numbers / Year</b>	<b>Depth to Basalt Rock</b>	<b>RQD<sup>2</sup> / UCS<sup>3</sup></b>	<b>Overburden Fill and Natural Soil Conditions Summary</b>	<b>Ground water</b>
GeoEngineers	B-401 to B-403 / 2005	7 - 12 feet bgs <sup>1</sup>	RQD - 0 to 97 percent UCS - 3,500 to 39,900 psi	Overburden - silt with sand; sand and gravel with occasional cobbles and variable silt content	Perched groundwater at interface between overburden and basalt.
GeoEngineers	TP-B7 and -B8; TP-C1, -C3, and -C5 to -C7; TP-D5, -D6 and -D8; TP-E4 and -E7; TP-F1, -F2, -F4 to F7; TP-G3, -G4, -G6 / 2004	2 - 9½+ feet bgs		Fill - gravel with sand, trace silt and construction debris. Overburden - gravel with sand, trace silt and occasional cobbles; sand with trace silt	Perched groundwater at interface between fill/overburden and basalt.
GeoEngineers	B-201 to B-215 / 2002	2 - 23½ feet bgs	RQD - 0 to 100 UCS - 6,000 to 32,000 psi	Fill - sand with gravel, cobbles and variable silt content; gravel with sand, cobbles and construction debris. Overburden - gravel with sand and variable silt content; sand with gravel and variable silt content	Perched groundwater at interface between fill/overburden and basalt.
AGRA Earth & Environmental	BH-A to BH-H / 1995	Not encountered to depths between ½ and 12½ feet bgs		Fill - gravel; silty sandy gravel. Overburden - sandy silt; silty sandy gravel; sand	~ 10½ feet bgs
Lambert Group	SH-01 to SH21 / 1993	1 - 21+ feet bgs		Overburden - sandy gravel with basalt fragments	9 - 11 feet bgs
Applied Geotechnology, Inc.	TP-1 to TP-5 / 1992	Not measured		Fill - silty sand with gravel and debris; gravelly sand with debris; sand with gravel and debris.	Not encountered


**Notes:**

1. bgs denotes 'below ground surface'
2. RQD - Rock Quality Designation - length of recovered drill core pieces in excess of 4 inches relative to the total length core drilled, in percent.
3. UCS - Unconfined Compressive Strength of rock in pounds per square inch (psi).




Map Revised: 12/05/2012 CRC

Path: W:\Spokane\Projects\1212088001\06\GIS\12088001\06\_VML\_F1.mxd



Sources: Esri, DeLorme, NAVTEQ, USGS, Intermap, iPC, NRCAN, Esri Japan, METI, Esri China (Hong Kong), Esri (Thailand), TomTom, 2012



**Vicinity Map**


**Proposed Convention Center Completion Project  
Spokane, Washington**



**Figure 1**

Notes:  
 1. The locations of all features shown are approximate.  
 2. This drawing is for information purposes. It is intended to assist in showing features discussed in an attached document. GeoEngineers, Inc. cannot guarantee the accuracy and content of electronic files. The master file is stored by GeoEngineers, Inc. and will serve as the official record of this communication. Data Sources: ESRI Data & Maps, Street Maps 2008. Projection: NAD 1983, UTM Zone 11 North.

OFFICE: SPO Dwg name: \\SPO\projects\12\12088001\06\CAD\04\_Sheet Files\1208800106-F2GT.dwg User: mformolo Plot time: Jan-14-13 @ 2:13pm



EXPLANATION:

- ⊕ B-401 GEOTECHNICAL SOIL BORING NUMBER AND APPROXIMATE LOCATION (GEOENGINEERS, 2005)
- ⊕ TP-B7 ENVIRONMENTAL TEST PIT NUMBER AND APPROXIMATE LOCATION (GEOENGINEERS, 2004)
- ⊕ B-201 ENVIRONMENTAL SOIL BORING NUMBER AND APPROXIMATE LOCATION (GEOENGINEERS, 2002)
- ⊕ MW 213 ENVIRONMENTAL MONITORING WELL NUMBER AND APPROXIMATE LOCATION (GEOENGINEERS, 2002)
- BH-A PREVIOUS BORE HOLE NUMBER AND APPROXIMATE LOCATION (AGRA, 1995)
- 3 PREVIOUS SOIL BORING NUMBER AND APPROXIMATE LOCATION (LAMBERT, 1993)
- TP-1 PREVIOUS TEST PIT NUMBER AND APPROXIMATE LOCATION (AGI, 1992)



Notes

1. The locations of all features shown are approximate.
2. This drawing is for information purposes. It is intended to assist in showing features discussed in an attached document. GeoEngineers, Inc. cannot guarantee the accuracy and content of electronic files. The master file is stored by GeoEngineers, Inc. and will serve as the official record of this communication.

Reference: Base drawing provided by LMN Architects titled "Spokane Convention Center Expansion" dated 2/2/04.

<b>Site Plan</b>	
Convention Center Completion Project Spokane, Washington	
<b>GEOENGINEERS</b>	<b>Figure 2</b>






**APPENDIX A**  
**Existing Exploration Logs**

**GEOENGINEERS 2005**

Date(s) Drilled	08/10/05	Logged By	DRB	Checked By	LDS
Drilling Contractor	GeoEngineers	Drilling Method	Hollow-Stem Auger/NX Core	Sampling Methods	SPT/Rockcore
Auger Data	3 3/4-inch ID	Hammer Data	140 lb hammer/30 in drop	Drilling Equipment	CME 75
Total Depth (ft)	34	Surface Elevation (ft)	Not measured	Approximate Groundwater Level (ft. bgs)	9



V6\_GTBORING\_P:\00101\1004707\FINALS\1011004707.GPJ\_GEIV6\_1.GDT\_9/13/05

### LOG OF BORING B-401



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-07

Figure: A-3  
 Sheet 1 of 2

V6 GTBORING P:\00011004707\FINAL\S011004707.GPJ GEIV6 1.GDT 9/13/05

Elevation feet	Depth feet	SAMPLES					MATERIAL DESCRIPTION	Moisture Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
		Interval Recovered (in)	Blows/foot	Sub-Sample Sample Number	Water Level	Graphic Log				
	25	60		8			Grades to joints planar, rough, yellow-green mineralized surfaces, inclined 45 to 50 degrees, spaced 8 to 12 inches			REC=98% RQD=100%
	30	57		9			Grades to joints spaced 16 inches apart		169	REC=86% RQD=74%
	35						Boring completed at approximately 34 foot depth Groundwater encountered at approximately 9 foot depth during drilling			* presumptive unconfined compressive strength of rock core
	40									
	45									
	50									

**LOG OF BORING B-401 (continued)**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-07

Figure: A- 3  
 Sheet 2 of 2

Date(s) Drilled	08/11/05	Logged By	DRB	Checked By	LDS
Drilling Contractor	GeoEngineers	Drilling Method	Hollow-Stem Auger/NX Core	Sampling Methods	SPT/Rockcore
Auger Data	3 3/4-inch ID	Hammer Data	140 lb hammer/30 in drop	Drilling Equipment	CME 75
Total Depth (ft)	30.5	Surface Elevation (ft)	Not measured	Approximate Groundwater Level (ft. bgs)	7.5

Elevation feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Moisture Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
	Depth feet	Interval Recovered (in)	Blows/foot	Sub-Sample Number							
0						AC	3 inches asphalt concrete pavement				
5	8	38	1			GW	Dark gray fine to coarse gravel with sand and occasional cobbles (dense, moist)				
10	18	0	2			ML	Brown silt with fine sand (very soft, wet)				
15	44		3			BRX	Fractured and weathered basalt; dark gray; stained state; fine-grained; rebound quality; open 2-dimensional planar to undulating, rough joints, surfaces stained with orange Fe-oxide; joints near-horizontal; spaced 8 inches to 10 inches, joints spaced 0.5 inches to 1.0 inches; CAD0				REC=98% RQD=82%
20	60		4			BRX	Basalt; dark gray; visually fresh; joints stained with green to yellow mineralization; inclined at 35 to 45 degrees and near-horizontal numerous healed joints inclined 70 to 90 degrees; joints spaced 12 inches to 24 inches; unit weight=171 pcf; BADA		171		REC=100% RQD=88%
25	59		5				Grades to joints spaced 10 inches to 20 inches; planar, rough, mineralized surfaces				REC=100% RQD=97%

V6\_GTBORING P:\000\0110047\07\FINALS\011004707.GPJ GEIV6 1.GDT 9/13/05

### LOG OF BORING B-402



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-07

Figure: A-4  
 Sheet 1 of 2

V6\_GTBORING P:\00011004707\FINALS\011004707.GPJ GEIV6 1.GDT 9/13/05

Elevation feet	SAMPLES					MATERIAL DESCRIPTION	Moisture Content %	Dry Unit Weight, lbs/ff <sup>3</sup>	OTHER TESTS AND NOTES
	Depth feet	Interval	Recovered (in)	Blows/foot	Sub-Sample Sample Number				
25		60			6				UCC*=39,000 psi REC=100% RQD=93%
30	<p>Boring completed at approximately 30 1/2 foot depth Groundwater encountered at approximately 7 1/2 foot depth during drilling</p>								
35									
40									
45									
50									

\* presumptive unconfined compressive strength of rock core

**LOG OF BORING B-402 (continued)**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-07

Date(s) Drilled	08/12/05	Logged By	DRB	Checked By	LDS
Drilling Contractor	GeoEngineers	Drilling Method	Hollow-Stem Auger/NX Core	Sampling Methods	SPT/Rockcore
Auger Data	3 3/4-inch ID	Hammer Data	140 lb hammer/30 in drop	Drilling Equipment	CME 75
Total Depth (ft)	30	Surface Elevation (ft)	Not measured	Approximate Groundwater Level (ft. bgs)	Not Encountered

Elevation feet	Depth feet	SAMPLES			Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Moisture Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
		Interval	Recovered (in)	Blows/foot							
0						CC	4 inches portland cement concrete pavement				
						SW-SM	Brown fine to coarse sand with silt, gravel and occasional cobbles (very dense, moist)				
	9		72								
	5										
						BRX	Fractured and weathered basalt; dark gray; stained state; fine-grained; rebound quality; open, planar to undulating, 2- and 3-dimensional rough joints with orange Fe-oxide staining; joints spaced 2 inches to 12 inches; inclined 30 to 50 degrees, near-horizontal, and 70 to 90 degrees; CAE0			REC=87% RQD=52%	
	36										
	10										
	58									REC=96% RQD=89%	
	15										
	59					BRX	Basalt; dark gray; visually fresh state, fine-grained; rebound quality open 2-dimensional joints stained with green mineralization; joints spaced 4 inches to 10 inches; unit weight=169 pcf; BAEA			REC=98% RQD=73%	
	20									UCC*=35,000 psi	
	60									REC=100% RQD=75%	

V6 GTBORING P:\00011004707\FINALS\011004707.GPJ GEIV6\_1.GDT 9/13/05

**LOG OF BORING B-403**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-07

Figure: A- 5  
 Sheet 1 of 2

V6\_GTBORING P:\00011004707\FINALS\011004707.GPJ GEIV6\_1.GDT 9/13/05

Elevation feet	SAMPLES					MATERIAL DESCRIPTION	Moisture Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
	Depth feet	Interval Recovered (in)	Blows/foot	Sub-Sample Sample Number	Water Level Graphic Log				
25	54		6					169	REC=100% RQD=51%
30	<p>Boring completed at approximately 30 foot depth            No groundwater observed to 7 feet below ground surface            Below 7 feet unable to distinguish groundwater from drilling fluid</p>								
35									
40									
45									
50									

**LOG OF BORING B-403 (continued)**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-07

**GEOENGINEERS 2004**

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	HeadSpace Vapor TLV(ppm)	NOTES
0					AC	2 inches asphalt concrete pavement			
					GP	Dark brown fine to coarse gravel with sand, trace silt and construction debris (medium dense, moist) (fill)			
						6 inch layer of black cinder	NS	0.6	
					GP	Tan fine to coarse gravel with sand and trace silt (medium dense, moist)			
						4 inch layer of white caliche	NS	0.9	
						Test pit completed at approximately 8 foot depth Rapid groundwater seepage observed at approximately 8 foot depth No caving observed			

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-B7**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-2  
 Sheet 1 of 1

0110-047-02 GEL\_ENVTESTPIT\_2.1.0 P:\00\0110047\02\FINALS\0110047.GPJ GEIV2\_2.GDT 4/7/04

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extindahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
0					AC	2 inches asphalt concrete pavement			
					GP	Gray fine gravel with sand (medium dense, dry)			
					GP	Brown gravel with sand, trace silt and construction debris (medium dense, moist) (fill)	NS	0.6	
					GP	Brown fine to coarse gravel with sand and trace silt (medium dense, moist)	NS	0.6	
						Test pit completed at approximately 8 1/2 foot depth Rapid groundwater seepage observed at approximately 8 foot depth No caving observed			

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-B8**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-8  
 Sheet 1 of 1

0110-047-02\_GEI\_ENVTESTPIT\_2.1.0\_P:\000110047\02\FINALS\0110047.GPJ\_GEIV2\_2\_GDT\_4/7/04

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	HeadSpace Vapor TLV(ppm)	NOTES
0					AC	2 inches asphalt concrete pavement			
					GP	Black gravel with sand, trace silt and construction debris (medium dense, moist) (fill)			
					SP	Brown fine sand with trace silt (loose, moist)	NS	0.7	
							NS	0.5	
						Test pit terminated at approximately 9 foot depth due to refusal on basalt rock Rapid groundwater seepage observed below approximately 7 foot depth No caving observed			

Note: See Figure B-2 for explanation of symbols

0110-047-02 GEI ENVTESTPIT\_2.1.0 P:\0010110047\02\FINALS\0110047.GPJ GEI\_V2\_2.GDT 4/7/04

**LOG OF TEST PIT TP-C1**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-4  
 Sheet 1 of 1

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extindahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample	Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
0						AC	2 inches asphalt concrete pavement			
						GP	Brown fine to coarse gravel with sand, trace silt and construction debris (medium dense, moist) (fill)			
								NS	0.7	
						SP	Brown fine sand with trace silt (loose, moist)			
								NS	0.7	
							Test pit completed at approximately 9 foot depth Rapid groundwater seepage observed below approximately 8 1/2 foot depth No caving observed			
10										
15										
20										

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-C3**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-5  
 Sheet 1 of 1


0110-047-02\_GEI\_ENVTESTPIT\_2.1.0\_P:\0010047\02\FINALS\0110047.GPJ GEIV2.2.GDT 4/7/04

Date Excavated: 03/18/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample	Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	HeadSpace Vapor TLV(ppm)	NOTES
0						AC GP	2 inches asphalt concrete pavement Brown fine to coarse gravel with sand, trace silt and large chunks of concrete with rebar (medium dense, moist) (fill)			
							Test pit terminated at approximately 3 1/2 foot depth due to backhoe refusal on concrete slab No groundwater seepage observed No caving observed	NS		

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-C5**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-6  
 Sheet 1 of 1

0110-047-02\_GEI\_ENVTESTPIT\_2.1.0\_P:\00\0110047\02\FINAL\S0110047.GPJ\_GEIV2\_2.GDT\_4/7/04



Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample	Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	HeadSpace Vapor TLV(ppm)	NOTES
0						AC	2 inches asphalt concrete pavement			
						GP	Gray fine gravel with sand (medium dense, dry)			
						GP	Brown fine to coarse gravel with sand and cobbles (medium dense, moist) (fill)			
						GP	Black fine to coarse gravel with sand and trace silt (medium dense, moist) (fill)	NS	1.1	
						GP	Light brown fine to coarse gravel with sand and trace silt (medium dense, moist) (fill)			
						GP	Black fine to coarse gravel with sand, trace silt and ash (medium dense, moist) (fill)	NS	0.5	
						GM	Tan fine to coarse gravel with sand (medium dense, moist)	NS	0.5	
							Test pit completed at approximately 9 1/2 foot depth Rapid groundwater seepage observed at approximately 9 1/2 foot depth Minor caving observed			

Note: See Figure B-2 for explanation of symbols

0110-047-02\_GEL\_ENVTESTPIT\_2.1.0\_P:\0010047\02\FINALS\0110047.GPJ\_GEIV2\_2.GDT\_4/7/04

**LOG OF TEST PIT TP-C7**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-8  
 Sheet 1 of 1

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	HeadSpace Vapor TLV(ppm)	NOTES
0					AC	2 inches asphalt concrete pavement			
					GP	Gray fine gravel with sand (medium dense, dry)			
					GP	Dark brown fine to coarse gravel with sand, trace silt and construction debris (very dense, moist) (fill)	NS	0.7	
					GP	Light brown fine to coarse gravel with sand and trace silt (medium dense, moist)	NS	0.6	
						Grades to loose	NS	0.8	
						Test pit completed at approximately 9 foot depth No groundwater seepage observed No caving observed			

Note: See Figure B-2 for explanation of symbols

0110-047-02 GEI\_ENVTESTPIT\_2.1.0 P:\100\0110047\02\FINAL\S0110047.GPJ GEIV2\_2.GDT 4/7/04

**LOG OF TEST PIT TP-D5**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-9  
 Sheet 1 of 1

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample	Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
0						CC	2 inches asphalt concrete pavement			
						GP	Gray fine gravel with sand (medium dense, dry)			
						GP	Dark brown fine to coarse gravel with sand, trace silt and construction debris (very dense, moist) (fill)			
	5						Test pit terminated at approximately 3.7 foot depth due to backhoe refusal on concrete slab No groundwater seepage observed No caving observed			
	10									
	15									
	20									

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-D5A**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-10  
 Sheet 1 of 1


0110-047-02\_GEL\_ENVTESTPIT\_2.1.0\_P:\00\0110047\02\FINAL\S0110047.GPJ GEIV2\_2.GDT 4/7/04

Date Excavated: 03/18/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample	Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLY(ppm)	NOTES
0						AC GP	2 inches asphalt concrete pavement Black fine to coarse gravel with sand, trace silt and coal dust (medium dense, moist) (fill)			
						GP	Brown fine to coarse gravel with sand and trace silt (medium dense, moist)	NS		
							Test pit completed at approximately 7 foot depth No groundwater seepage observed Severe caving observed			

Note: See Figure B-2 for explanation of symbols

0110-047-02\_GEL\_ENVTESTPIT\_2.1.0\_P:\0000110047\02\FINALS\0110047.GPJ\_GEIV2\_2.GDT\_4/7/04

**LOG OF TEST PIT TP-D6**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-11  
 Sheet 1 of 1

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample	Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
0						AC	2 inches asphalt concrete pavement			
						GP	Gray fine gravel with sand (medium dense, dry)			
						GP	Brown fine to coarse gravel with sand and trace silt (medium dense, moist)	NS	0.8	
							Test pit terminated at approximately 2 foot depth due to backhoe refusal on basalt rock No groundwater seepage observed No caving observed			

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-D8**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-12  
 Sheet 1 of 1

0110-047-02\_GEL\_ENVTESTPIT\_2.1.0\_P:\000110047\02\FINALS\0110047.GPJ\_GEIV2\_2.GDT\_4/7/04

Date Excavated: 03/18/04

Logged by: MBE

Equipment: CAT 420 Extindahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Shoen	Headspace Vapor TLV(ppm)	NOTES
0					AC GP	2 inches asphalt concrete pavement Brown fine to coarse gravel with sand and trace silt (medium dense, moist) (fill)			
							NS		
	5					Test pit terminated at approximately 2 1/2 foot depth due to backhoe refusal on basalt rock No groundwater seepage observed No caving observed			
10									
15									
20									

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-E4**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-13  
 Sheet 1 of 1

0110-047-02\_GEL\_ENVTESTPIT\_2.1.0\_P:\00010047\02\FINAL\S0110047.GPJ\_GEIV2\_2.GDT\_4/7/04



Date Excavated: 03/18/04

Logged by: MBE

Equipment: CAT 420 Extindahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
0					AC GP	2 inches asphalt concrete pavement Brown fine to coarse gravel with sand, trace silt and construction debris (medium dense, moist) (fill)			
							NS		
							NS		
5									
						Test pit terminated at approximately 5 foot depth due to backhoe refusal on basalt rock No groundwater seepage observed No caving observed			
10									
15									
20									

Note: See Figure B-2 for explanation of symbols

0110-047-02\_GEL\_ENVTESTPIT\_2.1.0\_P:\0010110047\02\FINALS\0110047.GPJ GEIV2\_2.GDT 4/7/04

**LOG OF TEST PIT TP-F1**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02


Figure: B-15  
 Sheet 1 of 1

Date Excavated: 03/18/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample	Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
0						AC GP	2 inches asphalt concrete pavement Dark brown fine to coarse gravel with sand, cobbles, trace silt and construction debris (medium dense, moist)	NS		
	5						Test pit terminated at approximately 3 foot depth due to backhoe refusal on bedrock No groundwater seepage observed No caving observed			
10										
15										
20										

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-F2**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-16  
 Sheet 1 of 1

0110-047-02\_GEL\_ENVTESTPIT\_2.1.0\_P:\000\0110047\02\FINALS\0110047.GPJ\_GEIV2\_2.GDT\_4/7/04

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
0					AC	2 inches asphalt concrete pavement			
					GP	Dark brownish black fine to coarse gravel with sand, trace silt and construction debris (medium dense, moist) (fill)			
					GP	Tan fine to coarse gravel with sand and trace silt (medium dense, moist)	NS		
							NS		
						Test pit terminated at approximately 7 1/2 foot depth due to backhoe refusal on bedrock No groundwater seepage observed No caving observed			

Note: See Figure B-2 for explanation of symbols

0110-047-02 GEI ENVTESTPIT 2.1.0 P:\00010110047\02\FINALS\0110047.GPJ GEIV2\_2.GDT 4/7/04

**LOG OF TEST PIT TP-F4**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-17  
 Sheet 1 of 1

Date Excavated: 03/18/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample	Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	HeadSpace Vapor TLV(ppm)	NOTES
0						AC GP	2 inches asphalt concrete pavement Dark brown fine to coarse gravel with sand, trace silt and construction debris (medium dense, moist) (fill)			
						BASALT	Dark gray fractured basalt (very dense, moist)	NS		
							Test pit terminated at approximately 5 foot depth due to backhoe refusal in basalt rock No groundwater seepage observed No caving observed			
5										
10										
15										
20										

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-F5**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-18  
 Sheet 1 of 1

0110-047-02\_GEL\_ENVTESTPIT\_2.1.0\_P:\00\0110047\02\FINALS\0110047.GPJ\_GEIV2\_2.GDT\_4/7/04

Date Excavated: 03/18/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample	Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
0						AC	2 inches asphalt concrete pavement			
						GP	Gray fine to coarse gravel with sand (medium dense, dry)			
							Test pit terminated at approximately 1/2 foot depth due to backhoe refusal on brick paving No groundwater seepage observed No caving observed			
5										
10										
15										
20										

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-F5A**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-19  
 Sheet 1 of 1

0110-047-02 GEI\_ENVTESTPIT\_2.1.0 P:\000110047\02\FINAL\S0110047.GPJ\_GEIV2\_2.GDT\_4/7/04

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
0				AC GP	AC GP	2 inches asphalt concrete pavement Dark brown fine to coarse gravel with sand, trace silt and construction debris (medium dense, moist) (fill)			
				BASALT	BASALT	Dark gray fractured basalt (very dense, moist)	NS		
						Test pit terminated at approximately 5 foot depth due to backhoe refusal in basalt rock No groundwater seepage observed No caving observed			

Note: See Figure B-2 for explanation of symbols

0110-047-02\_GEL\_ENVTESTPIT\_2.1.0\_P:\00\0110047\02\FINALS\0110047.GPJ\_GEIV2\_2.GDT\_4/7/04

**LOG OF TEST PIT TP-F6**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-20  
 Sheet 1 of 1

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	HeadSpace Vapor TLV(ppm)	NOTES
0					AC	2 inches asphalt concrete pavement			
					GP	Black fine to coarse gravel with sand and trace silt (medium dense, moist) (fill)			
					GP	Tan fine to coarse gravel with sand, trace silt and construction debris (medium dense, moist) (fill)	NS	0.6	
					BASALT	Dark gray fractured basalt (very dense, moist)			
						Test pit terminated at approximately 7 foot depth due to backhoe refusal in basalt rock No groundwater seepage observed No caving observed			

Note: See Figure B-2 for explanation of symbols

0110-047-02 GEI\_ENVTESTPIT\_2.1.0\_P:\000110047\02\FINAL\S01:10047.GPJ\_GEIV2\_2.GDT\_4/7/04

**LOG OF TEST PIT TP-F7**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-21  
 Sheet 1 of 1

Date Excavated: 03/18/04

Logged by: MBE

Equipment: CAT 420 Extindahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample	Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
	0					AC GP	2 inches asphalt concrete pavement Brown fine to coarse gravel with sand, trace silt and construction debris (medium dense, moist) (fill)	NS		
	5						Test pit terminated at approximately 2 foot depth due to backhoe refusal on basalt rock No groundwater seepage observed No caving observed			
	10									
	15									
	20									

Note: See Figure B-2 for explanation of symbols

0110-047-02 GEI\_ENVTESTPIT\_2.1.0 P:\0000110047\02\FINALS\0110047.GPJ GEIV2\_2.GDT 4/7/04

**LOG OF TEST PIT TP-G3**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-22  
 Sheet 1 of 1

Date Excavated: 03/18/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample	Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
0						AC GP	2 inches asphalt concrete pavement Brown fine to coarse gravel with sand, cobbles, and trace silt (medium dense, moist)			
							Test pit terminated at approximately 2 1/2 foot depth due to backhoe refusal on basalt rock No groundwater seepage observed No caving observed	NS		

Note: See Figure B-2 for explanation of symbols

0110-047-02\_GEL\_ENVTESTPIT\_2.1.0\_P:\000\0110047\02\FINAL\S\0110047.GPJ\_GEIV2\_2.GDT\_4/7/04

**LOG OF TEST PIT TP-G4**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-23  
 Sheet 1 of 1

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	HeadSpace Vapor TLV(ppm)	NOTES
0					AC GP	2 inches asphalt concrete pavement Black fine to coarse gravel with sand, cobbles and trace silt (medium dense, moist)			
							NS	0.5	
	5				BASALT	Dark gray fractured basalt (very dense, moist)			
	10					Test pit terminated at approximately 7 foot depth due to backhoe refusal in basalt rock No groundwater seepage observed No caving observed			
	15								
	20								

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-G6**



Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-24  
 Sheet 1 of 1

0110-047-02\_GEI\_ENVTESTPIT\_2.1.0\_P:\00\0110047\02\FINAL\S0110047.GPJ\_GEIV2\_2.GDT\_4/7/04

Date Excavated: 03/17/04

Logged by: MBE

Equipment: CAT 420 Extendahoe

Surface Elevation (ft): NM

Elevation feet	Depth feet	Sample Testing	Water	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	Headspace Vapor TLV(ppm)	NOTES
0	0				AC GP	<p>2 inches asphalt concrete pavement</p> <p>Gray fine gravel with sand (medium dense, dry to moist)</p> <p>Test pit terminated at approximately 1/2 foot depth due to backhoe refusal on brick paving</p> <p>No groundwater seepage observed</p> <p>No caving observed</p>			

Note: See Figure B-2 for explanation of symbols

**LOG OF TEST PIT TP-G6A**




Project: Convention Center Expansion  
 Project Location: Spokane, Washington  
 Project Number: 0110-047-02

Figure: B-26  
 Sheet 1 of 1

0110-047-02\_GEL\_ENVTESTPIT\_2.1.0\_P100011004702\FINAL\S0110047.GPJ\_GEIV2\_2.GDT\_4/7/04

## **GEOENGINEERS 2002**

Date(s) Drilled	06/25/02	Logged By	LDS	Checked By	CAS
Drilling Contractor	GeoEngineers, Inc.	Drilling Method	Hollow-Stem Auger	Sampling Methods	SPT/Nx Coring
Auger Data	7 3/4" O.D.	Hammer Data	140# hammer, 30" drop	Drilling Equipment	CME-75
Total Depth (ft)	15	Surface Elevation (ft)	NA	Station:	NA
Datum/System	NA			Centerline Offset:	NA



0110-047-00 GEI GTBORING 2.1.0 P:\0000110047\00FINAL\SI0110047E.GPJ GENV2\_2.GDT 9/27/02

**LOG OF BORING B-201**



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-4  
 Sheet 1 of 1

Date(s) Drilled	06/27/02	Logged By	LDS	Checked By	CAS
Drilling Contractor	GeoEngineers, Inc.	Drilling Method	Hollow-Stem Auger	Sampling Methods	SPT/Nx Coring
Auger Data	7 3/4" O.D.	Hammer Data	140# hammer, 30" drop	Drilling Equipment	CME-75
Total Depth (ft)	23.5	Surface Elevation (ft)	NA	Station:	NA
Datum/System	NA			Centerline Offset:	NA

Elevation feet	Depth feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Water Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
		Interval	Testing/No.	Recovered (in)	Blows/foot							
0							AC	4 inches asphalt concrete				
	1				20		SP-SM	Brown to gray fine to coarse sand with silt, gravel, cobbles and occasional brick fragments (medium dense, moist) (fill)				
	2				20							
	3				13		SP	Brown to gray fine to coarse sand with gravel (medium dense, wet) (fill)				
	4				6		SM	Olive-green silty fine to coarse sand with gravel (medium dense, wet) (fill)				
	5				21							
	6				30/3"		GP-GM	Gray fine to coarse gravel with trace sand (medium dense, wet)				
	7						BRX	Gray basalt with small minor vesicles, stained state to visually fresh state, pit to rebound quality, with 3- to 2-dimensionaol planes of separation, unit weight not measured (CBEO to BADO)		177	UCC ~ 31 ksi Rec = 100%, RQD = 88 UCC ~ 31 ksi	
								Boring completed at approximately 23 1/2 foot depth on 06/27/02 Groundwater encountered at approximately 8 foot depth during drilling				

Note: See Figure A-2 for explanation of symbols

0110-047-00 GEI GTBORING 2.1.0 P:\000110047\00\FINALS\0110047E.GPJ GEIV2\_2.GDT 9/27/02

### LOG OF BORING B-202



Project:	Spokane Public Facilities District - Option 2 Site
Project Location:	Spokane, WA
Project Number:	0110-047-00

Figure: A-5  
Sheet 1 of 1

Date(s) Drilled	06/26/02	Logged By	LDS	Checked By	CAS
Drilling Contractor	GeoEngineers, Inc.	Drilling Method	Hollow-Stem Auger	Sampling Methods	SPT/Nx Coring
Auger Data	7 3/4" O.D.	Hammer Data	140# hammer, 30" drop	Drilling Equipment	CME-75
Total Depth (ft)	17	Surface Elevation (ft)	NA	Station:	NA
Datum/System	NA			Centerline Offset:	NA

Elevation feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Water Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
	Depth feet	Interval	Testing/No.	Recovered (in)							
0							AC	3 inches asphalt concrete			
1					10		GP	Brown fine gravel with sand, cobbles and construction debris (loose, moist) (fill)			
2					4		SM	Brown silty fine sand (very loose, moist to wet) (fill)			
3					0						
4					16		SP-SM	Brown fine to coarse sand with gravel (medium dense, wet)			
5					49		GP	Brown fine to coarse gravel with silt and sand (dense, wet)			
6					33 3/4"		BRX	Gray slightly vesicular basalt, stained to visually fresh state, pit to rebound quality with 3- to 2-dimensional planes of separation, unit weight not measured (CBEO to BADO)			UCC ~ 19 ksi Rec = 100%, RQD = 26 UCC ~ 26 ksi
7											
20								Boring completed at approximately 17 foot depth on 06/26/02 Groundwater encountered at approximately 5 1/5 foot depth during drilling			
25											
30											
35											
40											

Note: See Figure A-2 for explanation of symbols

0110-047-00 GEL\_GTBORING 2.1.0 P:\0010047\000\FINALS\0110047E.GPJ GEIV2 2.GDT 9/27/02

### LOG OF BORING B-203



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-6  
 Sheet 1 of 1

Date(s) Drilled	06/28/02	Logged By	LDS	Checked By	CAS
Drilling Contractor	GeoEngineers, Inc.	Drilling Method	Hollow-Stem Auger	Sampling Methods	SPT/Nx Coring
Auger Data	7 3/4" O.D.	Hammer Data	140# hammer, 30" drop	Drilling Equipment	CME-75
Total Depth (ft)	17.5	Surface Elevation (ft)	NA	Station:	NA
Datum/System	NA			Centerline Offset:	NA

Elevation feet	Depth feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Water Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
		Interval	Testing/No.	Recovered (in)	Blows/foot							
0							AC	4 inches asphalt concrete				
	1				22		GP-GM	Brown to gray fine to coarse gravel with silt, sand and brick fragments (loose to dense, dry) (fill)	5			
	2				7				8			
	3				28							
	4				43							
	5											
	6				2		SM	Gray silty fine to medium sand with occasional gravel (very loose, wet) (fill)				
	7				12							
	8				30/4"		GP-GM	Brown fine to coarse gravel with fine to coarse sand and silt (medium dense, wet)				
	9											
	10											
	11											
	12											
	13											
	14											
	15											
	16											
	17											
	18											
	19											
	20							Boring terminated at approximately 17 1/2 foot depth due to auger refusal on 06/28/02 Groundwater encountered at approximately 7 foot depth during drilling				
	21											
	22											
	23											
	24											
	25											
	26											
	27											
	28											
	29											
	30											
	31											
	32											
	33											
	34											
	35											
	36											
	37											
	38											
	39											
	40											

Note: See Figure A-2 for explanation of symbols

0110-047-00 GEI GTBORING 2.1.0 P:\001004700\FINALS\0110047E.GPJ GEIV2\_2.GDT 9/27/02

**LOG OF BORING B-204**



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-7  
 Sheet 1 of 1

Date(s) Drilled	07/02/02	Logged By	LDS	Checked By	CAS
Drilling Contractor	GeoEngineers, Inc.	Drilling Method	Hollow-Stem Auger	Sampling Methods	SPT/Nx Coring
Auger Data	7 3/4" O.D.	Hammer Data	140# hammer, 30" drop	Drilling Equipment	CME-75
Total Depth (ft)	27	Surface Elevation (ft)	NA	Station:	NA
Datum/System	NA			Centerline Offset:	NA

Elevation feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Water Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
	Depth feet	Interval	Testing/No.	Recovered (in)							
0						AC	2 inches asphalt concrete				
1					18	GP	Brown fine to medium gravel with silt, sand, cobbles and construction debris (medium dense, moist) (fill)				
2					18	GM	Dark brown silty fine to coarse gravel with sand and cobbles (loose to medium dense, moist) (fill)				
3					10		Becomes wet				
4					4						
5					30/1"						
6					21						
7					75						
8					10	GP	Brown to gray fine to coarse gravel with sand and cobbles (loose to medium dense, wet)				
9						GM	Gray silty fine to coarse gravel with sand and cobbles (very dense, wet)				
10					50/2"	BRX	Gray moderately vesicular basalt, stained to visually fresh state, pit quality with 3- to 2-dimensional planes of separation, unit weight not measured (CBE0 to BBDO)				Rec = 100%, RQD = 50
27							Boring completed at approximately 27 foot depth on 07/02/02 Groundwater encountered at approximately 8 foot depth during drilling				

Note: See Figure A-2 for explanation of symbols

0110-047-00 GEL GTBORING 2.1.0 P:\0010110047\00FINAL\S10110047E.GPJ GEIV2 2.GDT 9/27/02

### LOG OF BORING B-205



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-8  
 Sheet 1 of 1

Date(s) Drilled	06/26/02	Logged By	LDS	Checked By	CAS
Drilling Contractor	GeoEngineers, Inc.	Drilling Method	Hollow-Stem Auger	Sampling Methods	SPT/Nx Coring
Auger Data	7 3/4" O.D.	Hammer Data	140# hammer, 30" drop	Drilling Equipment	CME-75
Total Depth (ft)	16.5	Surface Elevation (ft)	NA	Station:	NA
Datum/System	NA			Centerline Offset:	NA

Elevation feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Water Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
	Depth Interval feet	Testing/No. Recovered (in)	Blows/foot								
0						AC	4 inches asphalt concrete				
1			30			GP	Gray to brown fine to coarse gravel with sand and trace silt (medium dense to dense, moist) (fill)				
2											
3			9			GP	Gray to coarse gravel with sand and trace silt (loose, wet)				
4			7								
5			15								
6						BRX	Light gray to gray moderatley vesicular basalt, stained state, pit quality with 3- to 2-dimensional planes of separation, unit weight not measured (CBEO to CBDO)		158		Rec = 78%, RQD = 0 Rec = 67%, RQD = 0 Rec = 50%, RQD = 0 UCC ~ 14 ksi
7											
8											
							Boring completed at approximately 16 1/2 foot depth on 06/26/02 Groundwater encountered at approximately 8 foot depth during drilling				
20											
25											
30											
35											
40											

Note: See Figure A-2 for explanation of symbols

0110-047-00 GEI GTBORING 2.1.0 P:\000110047\001\FINALS\0110047E.GPJ GEIV2 2.GSDT 9/27/02

### LOG OF BORING B-206



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-9  
 Sheet 1 of 1

Date(s) Drilled	07/03/02	Logged By	LDS	Checked By	CAS
Drilling Contractor	GeoEngineers, Inc.	Drilling Method	Hollow-Stem Auger	Sampling Methods	SPT/Nx Coring
Auger Data	7 3/4" O.D.	Hammer Data	140# hammer, 30" drop	Drilling Equipment	CME-75
Total Depth (ft)	2	Surface Elevation (ft)	NA	Station:	NA
Datum/System	NA			Centerline Offset:	NA

Elevation feet	Depth feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Water Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
		Interval	Testing/No.	Recovered (in)	Blows/foot							
0							AC SM	2 inches asphalt concrete Dark brown silty fine to coarse sand with gravel (medium dense, moist) (fill)				
				30/4"				Boring terminated at approximately 2 foot depth due to refusal on 07/03/02 No groundwater encountered during drilling				
5												
10												
15												
20												
25												
30												
35												
40												

Note: See Figure A-2 for explanation of symbols

0110-047-00 GEI\_GTBORING 2.1.0 P:\0010047\00FINAL\0110047E.GPJ GEV2 2.GDT 9/27/02

**LOG OF BORING B-207**



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-10  
 Sheet 1 of 1

Date(s) Drilled	07/03/02	Logged By	LDS	Checked By	CAS
Drilling Contractor	GeoEngineers, Inc.	Drilling Method	Hollow-Stem Auger	Sampling Methods	SPT/Nx Coring
Auger Data	7 3/4" O.D.	Hammer Data	140# hammer, 30" drop	Drilling Equipment	CME-75
Total Depth (ft)	11	Surface Elevation (ft)	NA	Station:	NA
Datum/System	NA			Centerline Offset:	NA

Elevation feet	Depth feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Water Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
		Interval	Testing/No.	Recovered (in)	Blows/foot							
0								2 inches asphalt concrete				
1				30/3"			AC	Dark brown silty fine to coarse sand with gravel (medium dense, moist) (fill)				
2							CC	6 inches concrete over 3 inches basalt				
3							SM	Brown silty sand with gravel (medium dense, moist)			Rec = 33%, RQD = 0	
5											UCC ~ 31 ksi	
10							BRX	Light gray moderately vesicular basalt, stained to visually fresh state, pit quality with 3- to 2-dimenaional planes of separation, unit weight not measured (CCCO to BBCO)		177	Rec = 24%, RQD = 0	
11								Boring completed at approximately 11 foot depth on 07/03/02			Rec = 100%, RQD = 0	
15								Groundwater not measured due to drill fluids			UCC ~ 6 ksi	
20											Rec = 100%, RQD = 21	
25												
30												
35												
40												

Note: See Figure A-2 for explanation of symbols

0110-047-00 GEI GTBORING 2.1.0 P:\0000110047\00\FINALS\0110047E.GPJ\_GEIV2\_2.GDT\_9/27/02

### LOG OF BORING B-207A



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-11  
 Sheet 1 of 1

Date(s) Drilled	06/28/02	Logged By	GDP	Checked By	MLB
Drilling Contractor	Enviornmental West	Drilling Method	Air Rotary	Sampling Methods	2.5" O.D. Split Spoon
Auger Data	NA	Hammer Data	140# hammer, 30" drop	Drilling Equipment	Schramm T300M Rota Drill
Total Depth (ft)	15	Surface Elevation (ft)	NA	Station:	NA
Datum/ System	NA			Centerline Offset:	NA

Elevation feet	Depth feet	SAMPLES			Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Water Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
		Interval	Testing/No.	Recovered (in)							
0						AC	2 inches asphalt concrete				
						SM	Brown silty fine to coarse sand with gravel (medium dense, dry to moist)				
						FILL	Concrete debris, wood and gravel				
	1			50/3"							
	2			68/6"							
5							Well rounded gravels				
	3			52							
	4			83		GM	Brown silty medium to coarse gravel with sand (very dense, moist)				
10											
						BRX	Basalt rock				
15							Boring completed at approximately 15 foot depth on 06/28/02				
							Groundwater encountered at approximately 9 1/2 foot depth during drilling				
20											

Note: See Figure A-2 for explanation of symbols

0110-047-00\_GEI\_GTBORING 2.1.0 P:\00\0110047\00\FINALS\0110047E.GPJ GEIV2\_2.GDT 9/27/02


### LOG OF BORING B-208



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-12  
 Sheet 1 of 1

Date(s) Drilled	06/28/02	Logged By	GDP	Checked By	MLB
Drilling Contractor	Environmental West	Drilling Method	Air Rotary	Sampling Methods	2.5" O.D. Split Spoon
Auger Data	NA	Hammer Data	140# hammer	Drilling Equipment	Schramm T300M Rota Drill
Total Depth (ft)	19.7	Surface Elevation (ft)	NA	Station:	NA
Datum/System	NA			Centerline Offset:	NA



Note: See Figure A-2 for explanation of symbols

### LOG OF BORING B-209



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-13  
 Sheet 1 of 1

0110-047-00 GEL GTEBORING 2.1.0 P:\00011004700\FINALS\0110047E.GPJ GEIV2\_2.GDT 9/27/02

Date(s) Drilled	06/27/02	Logged By	LDS	Checked By	CAS
Drilling Contractor	GeoEngineers, Inc.	Drilling Method	Hollow-Stem Auger	Sampling Methods	SPT/Nx Coring
Auger Data	7 3/4" O.D.	Hammer Data	140# hammer, 30" drop	Drilling Equipment	CME-75
Total Depth (ft)	12.25	Surface Elevation (ft)	NA	Station:	NA
Datum/System	NA			Centerline Offset:	NA

Elevation feet	Depth feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Water Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
		Interval	Testing/No.	Recovered (in)	Blows/foot							
0							AC	5 inches asphalt concrete				
	1				27		SM	Brown-gray silty fine to coarse sand with gravel (medium dense, dry to moist) (fill)	6		14% passing the U.S. No 200 sieve	
	2						CC	5 inches concrete			Rec = 89%, RQD = 39	
	3						BRX	Light gray to gray moderately vesicular basalt, stained state to visually fresh state, dent to pit quality with 3- to 2-dimensaional palnes of separation, unit weight not measured (CCEO to BBDO)			UCC ~ 25 ksi	
	4										Rec = 100%, RQD = 100	
								Boring completed at approximately 12.25 foot depth on 06/27/02			Rec = 100%, RQD = 100	
								Groundwater not measured due to drill fluids			UCC ~ 31 ksi	
15												
20												
25												
30												
35												
40												

Note: See Figure A-2 for explanation of symbols

0110-047-00 GEL GTBORING 2.1.0 P:\00\0110047\00\FINAL\S0110047E.GPJ GEIV2 2.GDT 9/27/02

### LOG OF BORING B-210



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-14  
 Sheet 1 of 1

Date(s) Drilled	07//02/02	Logged By	LDS	Checked By	CAS
Drilling Contractor	GeoEngineers, Inc.	Drilling Method	Hollow-Stem Auger	Sampling Methods	SPT/Nx Coring
Auger Data	7 3/4" O.D.	Hammer Data	140# hammer, 30" drop	Drilling Equipment	CME-75
Total Depth (ft)	13.5	Surface Elevation (ft)	NA	Station:	NA
Datum/ System	NA			Centerline Offset:	NA

Elevation feet	Depth feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Water Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
		Interval	Testing/No.	Recovered (in)	Blows/foot							
0							AC	2 inches asphalt concrete				
1					16		GP	Brown to gray fine to coarse gravel with sand, cobbles and trace silt (medium dense to very dense, moist)				
2					50/2"							
5							BRX	Light gray moderately vesicular basalt, stained state to visually fresh, dent quality with 3- to 2-dimensional planes of separation, separation to 8 feet where solids preferred breakage, unit weight not measured (CCC0 to BCBO)			Rec = 100%, RQD = 36 UCC ~ 27 ksi	
10											Rec = 100%, RQD = 44	
15										169	Rec = 100%, RQD = 94 UCC ~ 27 ksi	
20												
25												
30												
35												
40												
								Boring completed at approximately 13 1/2 foot depth on 07/02/02 Groundwater not measured due to drill fluids				

Note: See Figure A-2 for explanation of symbols

### LOG OF BORING B-211



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-15  
 Sheet 1 of 1

0110-047-00\_GEL\_GTBORING\_2.1.0\_P:\00011004700\FINALS\0110047E.GPJ GEI.V2\_2.GDT 9/27/02

Date(s) Drilled	06/25/02	Logged By	LDS	Checked By	CAS
Drilling Contractor	GeoEngineers, Inc.	Drilling Method	Hollow-Stem Auger	Sampling Methods	SPT/Nx Coring
Auger Data	7 3/4" O.D.	Hammer Data	140# hammer, 30" drop	Drilling Equipment	CME-75
Total Depth (ft)	12	Surface Elevation (ft)	NA	Station:	NA
Datum/System	NA			Centerline Offset:	NA

Elevation feet	Depth feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Water Content %	Dry Unit Weight, lbs/ft <sup>3</sup>	OTHER TESTS AND NOTES
		Interval	Testing/No.	Recovered (in)	Blows/foot							
0								2 inches asphalt concrete				
1				15/5"			AC GP	Brown fine to coarse gavel with silt, sand and cobbles (medium dense, dry to moist)			UCC ~ 16 ksi	
2							BRX	Gray vesicular basalt, visually fresh state, pit quality with 3- to 2-dimensional planes of separation, unit weight not measured (BBEO to BBDO)		171	Rec = 100%, RQD = 61	
3											Rec = 100%, RQD = 74	
4											Rec = 100%, RQD = 100	
5											Rec = 100%, RDD = 39	
10												
15								Boring completed at approximately 12 foot depth on 06/25/02				
								Groundwater not measured due to drill fluid				
20											UCC ~ 17.3 ksi	
25												
30												
35												
40												

Note: See Figure A-2 for explanation of symbols

0110-047-00\_GEL\_GTBORING 2.1.0 P:\0001\10047\00FINAL\SD1110047E.GPJ GEIV2\_2.GDT 9/27/02


### LOG OF BORING B-212



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-16  
 Sheet 1 of 1

Date(s) Drilled	06/27/02	Logged By	GDP	Checked By	MLB
Drilling Contractor	Environmental West	Drilling Method	Air Rotary	Sampling Methods	3" O.D. split spoon
Total Boring Depth (ft)	20	Hammer Data	140# hammer	Drilling Equipment	Schramm T300M Rota Drill
Well Depth (ft)	16	Top of Well Elevation (ft)		Groundwater Level (ft. bgs)	7.1



### LOG OF MONITORING WELL MW-213



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-17  
 Sheet 1 of 1

0110-047-00\_GEL\_ENVWELL\_2.1.0\_P:\000\110047\00\FINAL\S0110047E.GPJ\_GEIV2\_2.GDT\_9/27/02

Date(s) Drilled	06/27/02	Logged By	GDP	Checked By	MLB
Drilling Contractor	Environmental West	Drilling Method	Air Rotary	Sampling Methods	3" O.D. Split Spoon
Auger Data	NA	Hammer Data	140# hammer	Drilling Equipment	SchrammT300M Rota Drill
Total Depth (ft)	5	Surface Elevation (ft)	NM	Ground Water Level (ft. bgs)	NA
Datum/ System					

Elevation feet	Depth feet	SAMPLES			Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	PID Reading (ppm)	NOTES
		Interval	Testing/No. Recovered (in)	Blows/foot							
0						AC	3 inches of asphalt concrete underlain by 3 inches crushed top coarse (fill)				
	1		0	50/0**		GM	Cobbles with silt, sand and gravel (loose, dry to moist)	NS	0		
						BRX	Basalt bedrock	NS	0		
5							Boring completed at approximately 5 foot depth on 06/27/02 No groundwater encountered during drilling *Blow counts not representative because of coarse-grained nature of material				
10											
15											

Note: See Figure A-2 for explanation of symbols

### LOG OF BORING B-214



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-18  
 Sheet 1 of 1

Date(s) Drilled	06/27/02	Logged By	GDP	Checked By	MLB
Drilling Contractor	Environmental West	Drilling Method	Air Rotary	Sampling Methods	3" O.D. Split Spoon
Auger Data	NA	Hammer Data	140# hammer	Drilling Equipment	Schramm T300M Rota Drill
Total Depth (ft)	8	Surface Elevation (ft)	NM	Ground Water Level (ft. bgs)	NA
Datum/System					

Elevation feet	SAMPLES				Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	PID Reading (ppm)	NOTES
	Depth feet	Interval	Testing/No.	Recovered (in)							
0						AC	3 inches asphalt concrete underlain by 3 inches crushed gravel top coarse (fill)				
						GP	Gray brown silty gravel (very dense, dry) (fill)	ss	0		Sample EB-6A-1.0
	CA 1		11	100/6**		SM	Brown silty fine to coarse sand with gravel (medium dense, dry) (fill)				
						BRX	Weathered basalt				
5							Competent basalt				
10							Boring completed at approximately 8 foot depth on 06/27/02 No groundwater encountered during drilling *Blow counts not representative because of coarse-grained nature of material				
15											

Note: See Figure A-2 for explanation of symbols

### LOG OF BORING B-214A



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-19  
 Sheet 1 of 1

0110-047-00\_GEL ENVBORING 2.1.0\_P:1001011004700FINAL\S0110047E.GPJ GEIV2 1.GDT 9/27/02

Date(s) Drilled	06/27/02	Logged By	GDP	Checked By	MLB
Drilling Contractor	Environmental West	Drilling Method	Air Rotary	Sampling Methods	3" O.D. Split Spoon
Auger Data	NA	Hammer Data	140# hammer	Drilling Equipment	Schramm T300M Rota Drill
Total Depth (ft)	9	Surface Elevation (ft)	NM	Ground Water Level (ft. bgs)	NA
Datum/System					

Elevation feet	Depth feet	SAMPLES			Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	PID Reading (ppm)	NOTES
		Interval	Testing/No. Recovered (in)	Blows/foot							
0						AC	3 inches asphalt concrete over 3 inches crushed gravel top coarse				
	1		0	50/2"		FILL	4-inch-thick concrete slab with occasional asphalt and other construction debris (fill)				
	2		0	50/0"							
5						BRX	Basalt slightly weathered  Becomes competent				
10							Boring completed at approximately 9 foot depth on 06/27/02 No groundwater encountered during drilling				
15											

Note: See Figure A-2 for explanation of symbols

0110-047-00\_GEL\_ENVBORING 2.1.0 P:\000\0110047\00\FINALS\0110047E.GPJ\_GENV2\_1.GDT 9/27/02

### LOG OF BORING B-215



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-20  
 Sheet 1 of 1

Date(s) Drilled	06/27/02	Logged By	GDP	Checked By	MLB
Drilling Contractor	Environmental West	Drilling Method	Air Rotary	Sampling Methods	3" O.D. Split Spoon
Auger Data	NA	Hammer Data	140# hammer	Drilling Equipment	Schramm T300M Rota Drill
Total Depth (ft)	10.5	Surface Elevation (ft)	NM	Ground Water Level (ft. bgs)	NA
Datum/ System					

Elevation feet	Depth feet	SAMPLES			Water Level	Graphic Log	Group Symbol	MATERIAL DESCRIPTION	Sheen	PID Reading (ppm)	NOTES
		Interval	Testing/No.	Recovered (in)							
0						AC	3 inches asphalt concrete over 3 inches crushed gravel top coarse				
						FILL	Construction debris consisting of bricks and concrete, very little soil (dense, dry) (fill)				
		CA 1	6	66				NR	0	Sample EB-8A-1	
		CA 2	6	25		SM	Gray-brown silty medium to coarse sand with gravel (medium dense, moist) (fill)	NR	0	Sample EB-8A-3.5	
5			3	0	60/5"		Possible debris filled basement	NR	NR		
			4	0	50/0"	BRX	Basalt, slightly weathered	NR	NR		
							Becomes competent				
10							Boring completed at approximately 10 1/2 foot depth on 06/27/02 Perched groundwater encountered at approximately 7 foot depth during drilling Perched groundwater was possibly trapped in basement and disappeared once bedrock was encountered				
15											

Note: See Figure A-2 for explanation of symbols

0110-047-00 GEI ENVBORING 2.1.0 P:\0001\10047\00\FINALS\0110047E.GPJ GEV2\_1.GDT 9/27/02

### LOG OF BORING B-215A



Project: Spokane Public Facilities District - Option 2 Site  
 Project Location: Spokane, WA  
 Project Number: 0110-047-00

Figure: A-21  
 Sheet 1 of 1

## **AGRA EARTH & ENVIRONMENTAL 1995**

PROJECT *Red Lion/Sheraton Hotel*

W.O. 21-8027


BORING NO. *BH-A*

DEPTH (feet)	SOIL DESCRIPTION	SAMPLE TYPE	SAMPLE NUMBER	BLOW COUNTS	OVM (PPM)	GROUND WATER	STANDARD PENETRATION RESISTANCE					TESTING	
							Blows per foot						
0	Approximate ground surface elevation:						0	10	20	30	40	50	
	0-2" Asphalt Gravel												HCID
	Hand sample of gravel at three feet	X	A-2		0								
	Boring terminated at approxiamtely 3 feet Refusal at 3 feet on basalt bedrock												
5													
10													
15													
20													
25													
30													

**LEGEND**

 2-inch OD split spoon sampler

 Grab Sample




**AGRA**  
**Earth & Environmental**  
 539 West Sharp, Suite D  
 Spokane, WA 99201

DEPTH (feet)	SOIL DESCRIPTION	SAMPLE TYPE	SAMPLE NUMBER	BLOW COUNTS	OYM (PPM)	GROUND WATER	STANDARD PENETRATION RESISTANCE						TESTING
							Blows per foot						
0	Approximate ground surface elevation:						0	10	20	30	40	50	
0-2"	Roots and topsoil												HCID
5	Very loose, moist, dark brown fine sandy SILT		B-1	4	0								
	Very dense, wet to saturated, brown fine SAND with trace silt		B-2	52/5	--								HCID
10	Boring terminated at approximately 8.8 feet Refusal on bedrock or rubble												
15													
20													
25													
30													

**LEGEND**

 2-inch OD split spoon sampler




**AGRA**  
**Earth & Environmental**  
 539 West Sharp, Suite D  
 Spokane, WA 99201

DEPTH (feet)	SOIL DESCRIPTION	SAMPLE TYPE	SAMPLE NUMBER	BLOW COUNTS	OVM (PFM)	GROUND WATER	STANDARD PENETRATION RESISTANCE					TESTING	
							Blows per foot						
0	Approximate ground surface elevation: 0-2" Asphalt/2-6" Pea gravel (Fill)						0	10	20	30	40	50	
	Boring terminated at approximately 6 inches due to running into storm drain												
5													
10													
15													
20													
25													
30													

**LEGEND**

 2-inch OD split spoon sampler




**AGRA**  
**Earth & Environmental**  
 539 West Sharp, Suite D  
 Spokane, WA 99201

DEPTH (feet)	SOIL DESCRIPTION	SAMPLE TYPE	SAMPLE NUMBER	BLOW COUNTS	OVM READING	GROUND WATER	STANDARD PENETRATION RESISTANCE						TESTING
							Blows per foot						
0	Approximate ground surface elevation: ' 0-2" Asphalt						0	10	20	30	40	50	
	Dense, damp, black, silty sandy GRAVEL	X	DI		5								METALS
	Boring terminated at approximately 2 feet Refusal on bedrock or rubble												
5													
10													
15													
20													
25													
30													

**LEGEND**

I 2-inch OD split spoon sampler

X Grab sample




**AGRA**  
**Earth & Environmental**  
 539 West Sharp, Suite D  
 Spokane, WA 99201

DEPTH (feet)	SOIL DESCRIPTION	SAMPLE TYPE	SAMPLE NUMBER	BLOW COUNTS	OVM (PPM)	GROUND WATER	STANDARD PENETRATION RESISTANCE					TESTING	
							Blows per foot						
0	Approximate ground surface elevation:						0	10	20	30	40	50	
	0-2" Asphalt												
	Gravel												
	Dense, damp, dark brown, silty fine sandy GRAVEL- chemical odor (FILL)	X	EI		123								8080 8010 8020
	Boring terminated at approxiamtely 3 feet Refusal on bedrock or rubble												
5													
10													
15													
20													
25													
30													

**LEGEND**

-  2-inch OD split spoon sampler
-  Grab sample




**AGRA**  
**Earth & Environmental**  
 539 West Sharp, Suite D  
 Spokane, WA 99201

DEPTH (feet)	SOIL DESCRIPTION	SAMPLE TYPE	SAMPLE NUMBER	BLOW COUNTS	OVM (PPM)	GROUND WATER	STANDARD PENETRATION RESISTANCE					TESTING	
							Blows per foot						
0	Approximate ground surface elevation:						0	10	20	30	40	50	
	0-2" Asphalt												
	Dense, dry, light brown, fine sandy GRAVEL	X	FI		0								8015
	Boring terminated at approximately 2.75 feet . Refusal on bedrock or rubble												
5													
10													
15													
20													
25													
30													

**LEGEND**

-  2-inch OD split spoon sampler
-  Grab sample




**AGRA**  
**Earth & Environmental**  
 539 West Sharp, Suite D  
 Spokane, WA 99201

DEPTH (feet)	SOIL DESCRIPTION	SAMPLE TYPE	SAMPLE NUMBER	BLOW COUNTS	OVM READING	GROUND WATER	STANDARD PENETRATION RESISTANCE					TESTING	
							Blows per foot						
0	Approximate ground surface elevation: 0-2" Asphalt Gravel (FILL)						0	10	20	30	40	50	
5	Very loose, damp, fine sandy SILT with trace gravel		G-1										8010 8020
10	Very loose, wet, brown, fine to medium SAND		G-2	ATD	--								
12.5	Boring terminated at approximately 12.5 feet Refussal on bedrock or rubble												
15													
20													
25													
30													

**LEGEND**

 2-inch OD split spoon sampler




**AGRA**  
**Earth & Environmental**  
 539 West Sharp, Suite D  
 Spokane, WA 99201

DEPTH (feet)	SOIL DESCRIPTION	SAMPLE TYPE	SAMPLE NUMBER	BLOW COUNTS	OVM (PPM)	GROUND WATER	STANDARD PENETRATION RESISTANCE					TESTING	
							Blows per foot						
0	Approximate ground surface elevation:						0	10	20	30	40	50	
	0-2" Asphalt Gravel												
	Dense, dry grading to damp, light brown, silty sandy GRAVEL	X	HI		0								8010 8020 8015
	Boring terminated at approximately 3 feet Refusal on bedrock or rubble												
5													
10													
15													
20													
25													
30													

**LEGEND**

 2-inch OD split spoon sampler

 Grab sample



**AGRA**  
**Earth & Environmental**  
 539 West Sharp, Suite D  
 Spokane, WA 99201

## **LAMBERT GROUP 1993**

# BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 26, 1993  
 P.N: E9338 Time In: 07:15 Time Out: 10:30  
 Owner: River Front Associates Observer: DEI  
 Project Type: Drill/Sampling/Monitoring Well Weather: Cool-Clear-45°  
 Boring No: SH-01 Boring Location: West end property near entrance to Hotel

Depth	Moisture	Field Observations	Sample #	Description
0 -	Dry	Asphalt from surface to 4" then from 4" to 5' Sand gravel	N/A	Reddish brown to light tan in color no odor noticeable
5 -	Damp	Sampled with split spoon HNU = 1ppm	SH01-1	Sandy Gravel Brown to light Tan-white in color
9 10 -	Damp Wet	Sampled with split spoon HNU = 1ppm	SH02-1	Sand dark in color no odor - Appears to be a coal seam(?)
11	Water	Water Table		Sand gravel - basalt fragments
20 - 21	T.D.			Drilled from 19 to 21 basalt Fresh basalt fragments

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 26, 1993  
 P.N: E9338 Time In: 11:00 Time Out: 13:00  
 Owner: Riverfront Associates Observer: DEL  
 Project Type: Drill / Sample Weather: 50° partly cloudy  
 Boring No: SH-02 Boring Location: East end of building - North west corner

0 -	slight	Asphalt 2 - 4 " below surface	N/A	Asphalt - sand - pea gravels
5 -	damp	split spoon HNU = 10 ppm	SH02 - 1	silt - sand - gravel Tan to brown in color / No odors
8 -	wet	water table	N/A	sand gravels
10 -		Bed rock	N/A	Fresh basalt
11 -	T.D.	Bed rock		Basalt fragments fresh
Depth	Moisture	Field Observations	Sample #	Description

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 26, 1993  
 P.N: E9338 Time In: 14:00 Time Out: 16:00  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: Partly cloudy  
 Boring No: SH03 Boring Location: South east corner of property

Depth	Moisture	Field Observations	Sample #	Description
0 -	Dry	Asphalt from surface to 4"	N/A	
2 -	slight	Fill material	SH03-1	sand gravel grab sample from two feet to three feet. No discoloration or odors.
5 -	T.D.	Basalt at three		Fresh basalt fragments from three feet.
-				
-				
-				
-				
-				

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: 4-26-93 & 4-27-93  
 P.N: E9338 Time In: 16:15 Time Out: 09:30  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: Rain - clearing  
 Boring No: SH04 Boring Location: 4' west of SH03

Depth	Moisture	Field Observations	Sample #	Description
0 -	Dry	Asphalt from surface to Approximately 4" bgs	N/A	Asphalt to 4" then sand & gravel to 4 feet. Sand and gravel is brown to tan in color. No odors.
4 -	dry	bedrock - basalt	N/A	switched over to down hole rotary hammer
5 -				
10 -				
20 -				
25 -	moist			damp area in basalt. Seep from rock - not water table.
30 -				
40 -	T.D.			Basalt bedrock from four feet to forty feet.

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 27, 1993  
 P.N: E9338 Time In: 10:30 Time Out: 11:00  
 Owner: River Front Associates Observer: DEI  
 Project Type: Drill Sample Weather: Partly cloudy  
 Boring No: SH05 Boring Location: NE property line ≈ 75 north of SH04

Depth	Moisture	Field Observations	Sample #	Description
0 -	dry to damp	Asphalt from 0 to 4" Sand gravel- from 4" Slight odor - HNU = 1ppm	N/A  SH05-1	Asphalt Sand gravel - brown to tan in color No discoloration
1 -	dry to damp	Basalt - Fresh	N/A	Bed rock
3 -	T.D.	Bedrock		Fresh basalt fragments
.				
.				
.				
.				

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 27, 1993  
 P.N: E9338 Time In: 11:30 Time Out: 12:40  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: Partly Cloudy  
 Boring No: SH06 Boring Location: Between TP2 & TP3

Depth	Moisture	Field Observations	Sample #	Description
0 -	Dry	Asphalt from 0 to 4" Sand and gravel to 2'	N/A	Brown to tan sand and gravel
2 -	Dry	Sampled cuttings - material appeared dark in color had an odor of Cresoles	N/A HNU = 10 - 15 ppm	
6 -	Dry	Split spoon sample Dark colored soil slight odor	HNU = 10 - 15 ppm SH06-1	Dark brown to black soil some white fragments noted in material, could be organic.
7 -	Dry	Basalt rock	N/A	Bedrock
8.5 -	T.D.	Basalt		Bedrock

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 27, 1993  
 P.N: E9338 Time In: 13:00 Time Out: 14:00  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: Partly Cloudy  
 Boring No: SH-07 Boring Location: Between TP4 & TP3

Depth	Moisture	Field Observations	Sample #	Description
0 -	Dry	Asphalt from 0 to 4"	N/A	
2 -	Dry	Brown to tan sand & gravel (split spoon)	SH07-2	Sand and gravel appears to be clean no odors present at 2" to 3"
3 -	Dry	railroad tie (?) wood fragments - no odor or discoloration	HNU = 1 ppm	
4 -	Dry	Basalt rock fresh angular fragments	N/A	Boulder
5 -	Dry	Softer material sand to silt	SH7-01 HNU = 1 ppm	Brown to dark brown soil to 5.5' Grab sample from cuttings
6 -	Dry	Fresh angular basalt	N/A	Dark colored basalt - fresh angular fragments
9 -	T.D.	Basalt bedrock		

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 27, 1993  
 P.N: E9338 Time In: 15:45 Time Out: 16:30  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill/Sample Weather: Cloudy  
 Boring No: SH08 Boring Location: North 50' from SH07

Depth	Moisture	Field Observations	Sample #	Description
0 -	Dry	Asphalt from 0 to 4"	N/A	Sand silt and gravel below 4"
3 -	Dry	Silt sand and gravels Split spoon sample	SH08-1 HNU = 1 ppm	Brown to tan silt sand and gravels No odors or discoloration
6 -	Dry	Conglomerate fragments and silty sand soil split spoon	SH08-2 HNU = 5 ppm	Silty to sandy soil - light brown to dark brown in color
7 -	Dry	Basalt rock fragments	N/A	Silty to sandy soil with basalt fragments (fresh)
8.5 -	T.D.	Basalt rock	N/A	Bedrock

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 27, 1993  
 P.N: E9338 Time In: 16:45 Time Out: 17:30  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: Cloudy  
 Boring No: SH09 Boring Location: = 60 to 75 feet east of SH06

0 -	Dry	Asphalt from 0 to 4"	N/A	Sand and gravel from 4" To 2'
2 -	Dry	Basalt rock fragments - sand and silt Split spoon	SH09-1 HNU = 1 ppm	No odor or discoloration noted
5 -	Damp	Sand and silt Split spoon	SH09-2 HNU = 1 ppm	Upper portion of sample was dark brown to black. No odor was noted.
7.5 -	T.D.	Drilling became hard at 5.5'	N/A	Fresh basalt fragments
Depth	Moisture	Field Observations	Sample #	Description

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 28, 1993  
 P.N: E9338 Time In: 08:00 Time Out: 08:30  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: High Clouds  
 Boring No: SH10 Boring Location: = 50' South of SH09

Depth	Moisture	Field Observations	Sample #	Description
0 -	Dry	Asphalt to 4"	N/A	
2 -	Moist	Sand - gravel Split spoon	N/A	Sand - gravel from cuttings. Split spoon only recovered rounded gravel no soil. No odor or discolor observed. Cuttings were tan to light brown in color.
5 -	Moist	Grab sample from drill cuttings	SH10-1	As above except fresh basalt rock fragments at 4.5'.
5.5 -	T.D.	No water		Fresh basalt outcrop

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 28, 1993  
 P.N.: E9338 Time In: 08:50 Time Out: 09:30  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / sample Weather: High Clouds  
 Boring No: SH11 Boring Location: = 50 feet south of SH06

Depth	Moisture	Field Observations	Sample #	Description
0 -	Dry	Asphalt from 0 to 4 "	N/A	Brown to tan silt sand gravel
2 -	Moist	Split spoon No odors	HNU = 1 ppm SH11-1	Dark brown sand - gravel. Some clay in sample. About 1%
5 -	Moist	No odors HNU = 1 ppm	N/A	Brown to tan gravels, sand & silt to 5'.
5.5 -	T.D.	Fresh basalt		Bedrock

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 28, 1992  
 P.N.: E9338 Time In: 10:05 Time Out: 11:00  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: High Clouds  
 Boring No: SH12 Boring Location: ≈ 50 Feet west of SH05

Depth	Moisture	Field Observations	Sample #	Description
0 -	Dry	Asphalt from 0 to 4"	N/A	
2 -	Moist	Split spoon	HNU = 2 ppm	No sample Cuttings showed tan to light brown sand gravel. No odor
5 -	Moist	Split spoon	SH12-1 HNU = 1 ppm	Brown to tan sand & gravel
8 -	Moist	Drill cuttings sampled Slight discoloration in cuttings	SH12-2	Light brown to dark brown sand-gravels with some clay.
8.5 -	T.D.			Basalt bed rock

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 28, 1993  
 P.N: E9338 Time In: 11:30 Time Out: 12:00  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / sample Weather: Cloudy  
 Boring No: SH13 Boring Location: = 50 feet south of SH07

Depth	Moisture	Field Observations	Sample #	Description
0 -	Dry	Asphalt from 0 to 4"	N/A	
2 -	Moist	Dark discoloration No odor	SH13-1 HNU = 2 ppm	Silt - Clay - Sand Brown to black sand silt and clay
2.5 -	Moist	Soil changed colors to more natural colors.	SH13-2 Grab	As above, except material is light brown to tan in color.
5 -	T.D.	Basalt		Bedrock

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 28, 1993  
 P.N: E9338 Time In: 12:00 Time Out: 12:40  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / sample Weather: Cloudy  
 Boring No: SH14 Boring Location: ≈ 40 feet south of SH13 on property line

0 -	Dry	Asphalt from 0 to 4"	N/A	
1 -	Moist	Sand - Silt - Clays	N/A	Brown in color no odor or discoloration
2 -	Moist	Sand - Gravels Split spoon	SH14-1	Brown to tan sand gravels with slight discoloration - no odor.
2.5 -	Dry	Fresh rock	N/A	Basalt rock fragments
3.5 -	T.D.			Basalt rock Bed rock
Depth	Moisture	Field Observations	Sample #	Description





## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 28, 1993  
 P.N: E9338 Time In: 15:35 Time Out: 16:25  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: Cloudy  
 Boring No: SH17 Boring Location: ≈ 45 feet south of SH15

Depth	Moisture	Field Observations	Sample #	Description
0 -	Damp	Asphalt from 0 to 4"	N/A	Brown to tan sand
2 -	Moist	Split spoon	SH17-1	Dark brown to black sand - silt - clay. No odors.
3.4 -	Moist	Split spoon	SH17-2	Dark brown to black clay soil. No odor.
6 -	Moist	Rock fragments		Fresh basalt
7.2 -	T.D.			Basalt bedrock

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 29, 1993  
 P.N: E9338 Time In: 08:30 Time Out: 09:10  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: Partly cloudy - Rain  
 Boring No: SH18 Boring Location: ≈ 50 north of SH08

Depth	Moisture	Field Observations	Sample #	Description
0 -	Wet	Asphalt from 0 to 4"		
1 -	Moist	No odors or discoloration	N/A	Sand gravel some silt and clay - brown to tan in color.
2 -	Moist	No odors or discoloration	N/A	Drill is bouncing having trouble penetrating. Soil is same as above:
3 -	Dry	Wood fragments	SH18-1 HNU = 1ppm	Railroad tie - sand - gravel - sand and gravel are dark colored. Some odor is present.
5 -	Moist	Split spoon	SH18-2 HNU = 1 ppm	Sand gravel are dark brown to black. No odors present.
5.5 -	Moist	Color change	N/A	Sand - gravel - silt brown to tan
6 -		Basalt fragments		Fresh angular fragments
7 -	T.D.	Basalt		Bed rock

## BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 29, 1993  
 P.N: E9338 Time In: 09:45 Time Out: 11:00  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: Cloudy & Rain  
 Boring No: SH19 Boring Location: ≈ 80 feet east of SH18

0 -	Wet	Asphalt from 0 to 4"		
1 -	Moist	Brown to tan		Sand - silt - gravel
2 -	Moist	Split spoon	SH19-1 HNU = 1 ppm	Gray to brown sand - silt - clay no odors - slight discoloration.
5 -	Moist	Split spoon	SH19-2 HNU = 1 ppm	Dark colored sand - gravel - clays
5.5 -				Soil is becoming lighter in color.
6 -	Damp			Pea gravel brown to tan in color.
8 -	Damp	Split spoon	SH19-3 HNU = 1 ppm	Brown to tan sand and gravels.
9 -	Wet	Water table		
12.5 -	T.D.	Basalt		Bed rock
Depth	Moisture	Field Observations	Sample #	Description

# BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 29, 1993  
 P.N: E9338 Time In: 11:35 Time Out: 14:20  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: Raining  
 Boring No: SH20 Boring Location: ≈ 50 feet east of SH19

0 -	Wet	Asphalt from 0 to 4"		
2 -	Moist	Dark brown clay	SH20-1	Grab sample from cuttings. Sample ranges from 2 feet to 4 feet.
5 -	Moist	Split spoon	SH20-2 HNU = 1 ppm	Dark discolored soil - No odors Soil is Black in color possibly oil or grease.
9 -	Moist to Damp			Soil appears the same as above
11 -	Wet	Water table		Water is dark in color
12 -				Water is cleaner in appearance.
21 -	T.D.			Did not reach bed rock Installed monitoring well
Depth	Moisture	Field Observations	Sample #	Description

# BORING/WELL LOG

Project: Sheraton-Spokane Hotel Date: April 29, 1993  
 P.N: E9338 Time In: 14:35 Time Out: 15:00  
 Owner: River Front Associates Observer: DEL  
 Project Type: Drill / Sample Weather: Raining  
 Boring No: SH21 Boring Location: North side of Hotel near Service Entrance

Depth	Moisture	Field Observations	Sample #	Description
0 -	Wet	Asphalt 0 to 4"		
2 -	T.D.			Brown to tan sand - gravel - clay  Hole stopped due to disturbance of meeting inside hotel.
-				
-				
-				
-				
-				

**APPLIED GEOTECHNOLOGY INC. 1992**

Laboratory  
Tests

Moisture  
Content


OWM

Depth

Sample

Test Pit Number 1

Date 12/10/92 Elevation \_\_\_\_\_




Asphaltic Concrete Pavement.

BROWN SILTY SAND (SM) medium dense, moist; fine to coarse grained, with some gravel, concrete, brick, and wood (Fill).

Groundwater not encountered during excavation.

Test Pit Number 2

Date 12/10/92 Elevation \_\_\_\_\_



Asphaltic Concrete Pavement.

BROWN GRAVELLY SAND (SW) medium dense, moist; fine to medium grained, with bricks, wood, and concrete (Fill).

Railroad ties at 4 feet.

BLACK SILTY SAND (SM) medium dense, moist; fine to medium grained, with some gravel (Fill).

Groundwater not encountered during excavation.



**Applied Geotechnology Inc.**

**Log of Test Pit 1 and 2**  
 Riverfront Associates/Sheraton-Spokane  
 Spokane, Washington

PLATE

**A2**

Laboratory Tests

Moisture Content


OVM

Depth

Sample

Test Pit Number 3


Date 12/10/92 Elevation \_\_\_\_\_



Asphaltic Concrete Pavement.  
 BROWN GRAVELLY SAND (SW) medium dense, moist; fine to medium grained, with brick and concrete (Fill).  
 Railroad Tie at 4 feet.  
 BLACK SILTY SAND (SM) medium dense, wet; fine to medium grained, with some gravel (Fill).

Test Pit Number 4

Date 12/10/92 Elevation \_\_\_\_\_



Asphaltic Concrete Pavement.  
 BROWN SAND (SP) medium dense, moist; fine to medium grained, with some gravel, cobbles, brick, and concrete (Fill).  
 Railroad tie at 4 feet.  
 LIGHT BROWN SILTY SAND (SM) medium dense, moist; fine to medium grained (Fill).  
 Groundwater not encountered during drilling.



**Applied Geotechnology Inc.**

**Log of Test Pit 3 and 4**  
 Riverfront Associates/Sheraton-Spokane  
 Spokane, Washington

PLATE

**A3**

JOB NUMBER  
15,710.001

DRAWN  
SES

APPROVED  
TSM

DATE  
5 Feb. 93

REVISED

DATE

Laboratory  
Tests

Moisture  
Content


OVM

Depth

Sample

Test Pit Number 5

Date 12/10/92 Elevation \_\_\_\_\_



Asphaltic Concrete Pavement.  
 BROWN SAND (SP) medium dense, moist; fine to medium grained, with  
 some gravel, brick, and concrete (Fill).  
 Concrete road with steel rails at 3 feet.  
 Groundwater not encountered during excavation.



Applied Geotechnology Inc.

Log of Test Pit 5  
 Riverfront Associates/Sheraton-Spokane  
 Spokane, Washington

PLATE

A4

JOB NUMBER  
15,710.001


DRAWN  
SES

APPROVED  
TSM


DATE  
5 Feb. 93

REVISED

DATE



**APPENDIX B**  
**Aquila GeoSciences, Inc. -**  
**Seismic Refraction Survey**



# AQUILA GEOSCIENCES, INC.

P.O. Box 544  
Potlatch, Idaho 83855  
(208) 875-1175

July 23, 2002

Mr. Christopher A. Sneider, P.E.  
Geotechnical Engineer  
GeoEngineers-Gifford  
523 East Second Avenue  
Spokane, Washington 99202

## Results of a Seismic Refraction Survey performed at Site 2, Proposed Spokane Convention Center Expansion, Spokane, Washington

### Introduction

Aquila Geosciences, Inc., conducted a seismic refraction survey, at your request, at Site 2 of the proposed Spokane Convention Center expansion in Spokane, Washington, on Saturday, July 20, 2002. The purpose of the survey was to determine depths to basalt "bedrock" and information on the basalt seismic velocities of the basalt to aid in GeoEngineer-Gifford's site characterization. Data were collected along two traverse lines. Line 3 ran from South to North and was 460 feet long. Line 4 ran from East to West and was 380 feet long. Chris Sneider provided assistance by barricading the survey line locations, helping lay out and pick up geophones, and providing traffic control during data acquisition.

### Data Acquisition

Seismic data were acquired using a Geometrics S-24 seismograph. We used a 12-pound sledge hammer beaten either directly against the asphalt pavement or against an aluminum plate as an energy source. Receivers were 10 Hz. vertical geophones spaced at 20-foot intervals. Shot point locations were selected to provide as much information about the overburden velocities as feasible given the budget, and coverage on the target refractor that would be adequate for data processing and interpretation using the Generalized Reciprocal Method (GRM) of interpreting seismic refraction data.

### Data Quality

The quality of the seismic data ranges from fair to poor. Noise, particularly noise from traffic and from the Spokane River, was a constant problem during data acquisition. There was both high frequency and low frequency noise present. To mitigate the effects of this noise we used a 100 Hz. low cut filter and a 250 Hz. high

cut filter (\*see footnote at end). We also placed shot points at 40 to 60 foot intervals along the seismic lines. This provided more information on overburden velocities, as well as much greater redundancy of arrival time data for the bedrock refractor. This increase in the number of arrival times from the bedrock refractor at each geophone provides a significant increase in the signal-to-noise ratio for the survey.

A second problem encountered at the site was the "pavement wave". The asphalt pavement acts as a wave guide for high frequency seismic energy. Since the seismic velocity of the asphalt is relatively high, this burst of energy tends to interfere with arrivals from the overburden. We dealt with this by basically disregarding the pavement wave and looking for a lower frequency minimum phase arrival within the pavement wave.

### Results and Interpretation

The seismic refraction data were processed and interpreted using the GRM (Generalized Reciprocal Method) of Palmer (1980). The results are shown in the accompanying tables, depth profiles, and velocity plots.

We treated the subsurface as a two layer case for the purposes of the interpretation. The first, upper, layer is "overburden", probably unconsolidated alluvium or fill that is unsaturated (at shallow depths) to saturated (at greater depths). This layer has a seismic velocity ranging from approximately 500 feet/second (south end of line 3) to approximately 2,500 feet/second (central part of line 4).

The second layer is basalt. The velocity of this layer is greater than 16,000 feet/second except for the westernmost 60 feet of line 4, where it appears to be about 12,300 feet/second.

Figures 1 and 2 show the depth profiles for lines 3 and 4, respectively, while tables 1 and 2 contain tabular information on depths and velocities. There is a fair amount of topography on the basalt surface in the survey area. The depths to bedrock calculated from the seismic data are consistent with the depth information from the boreholes drilled at the site, and the two data sets together provide an internally consistent interpretation of the configuration of the bedrock surface.

One word of caution is advised regarding depths to bedrock determined from the seismic data. The arcs on the depth profiles represent the distance from the geophone to the refractor surface (basalt, in this case). These arcs are actually slices of hemispheres taken in the place of the seismic line. There is an unstated assumption in the depth profile that the topography actually occurs in the place of the seismic section. If, however, bedrock is closer to a geophone at a point to the side of the line, the slant distance from the geophone to the bedrock surface is what will be calculated. It is therefore possible for the profiles to show a shallower depth

than is actually present directly below the line.

### Summary

The seismic refraction survey you requested that we perform at Site 2 of the planned Spokane Convention Center Expansion has been completed. The results of this survey are intended for use in project planning and management. We consider data derived from geophysical surveys as useful for supplementing and augmenting observations made by direct sampling techniques such as drilling or trenching. The geophysical surveys we do are intended to guide direct sampling, not replace it. Surveys are designed based on information known about the survey area prior to conducting the survey. All interpretations are opinions based on inferences from electrical measurements and the accuracy or correctness of such interpretations cannot be guaranteed. The interpretations apply only to the lines surveyed and features should not be extrapolated beyond or perpendicular to the surveyed line.

Please do not hesitate to call should you have any questions.

Sincerely,





Kent R. Johnson, Ph.D., P.G.  
Geologist/Geophysicist

**\* NOTE on filters:** The filter combination used during data acquisition at this site is rather extreme. We considered it advisable to use these filters because the noise problem was so bad. We also considered that it would be acceptable because the survey lines were short enough that phase rotations should not be a problem. The agreement between the calculated depths and the borehole information indicate this decision was justified.

### Reference Cited

Palmer, D., 1980, The Generalized Reciprocal Method of Seismic Refraction Interpretation: Soc. Expl. Geophysicists, Tulsa, 104 pp.

# Spokane Convention Center Expansion Site 2 Seismic Refraction Line 3





Vertical Exaggeration ~2.18:1

Figure 1

# Spokane Convention Center Expansion Site 2

## Seismic Refraction Line 4



Vertical Exaggeration ~1.94:1

TABLE 1

## Line 3 Depth and Velocity Results

Station	Ground Elevation	V1 (ft/sec)	V2 (ft/sec)	Depth to Top V2
0	0	534	16,203	2.2
20	0	596	16,203	4.3
40	0	657	16,203	4.9
60	0	810	16,203	5.9
80	0	964	16,203	7.5
100	0	1,117	16,203	9.8
120	0	1,025	16,203	10.0
140	0	934	16,203	10.0
160	0	1,040	16,203	11.4
180	0	1,146	16,203	13.7
200	0	1,125	16,203	11.9
220	0	1,103	16,203	13.4
240	0	1,265	16,203	18.5
260	0	1,427	16,203	20.1
280	0	1,568	16,203	22.9
300	0	1,687	16,203	22.3
320	0	1,624	16,203	21.3
340	0	1,560	16,203	21.6
360	0	1,601	16,203	20.9
380	0	1,641	16,203	21.3
400	0	1,681	16,203	22.6
420	0	1,721	16,203	23.4
440	0	1,761	16,203	20.3
460	0	1,802	16,203	20.5

TABLE 2

## Line 4 Depth and Velocity Results

Station	Ground Elevation	V1 (ft/sec)	V2 (ft/sec)	Depth to Top V2
0	0	939	16,880	12.1
20	0	1,109	16,880	13.7
40	0	1,280	16,880	15.5
60	0	1,696	16,880	19.0
80	0	2,112	16,880	21.3
100	0	2,528	16,880	24.0
120	0	2,328	16,880	20.9
140	0	2,129	16,880	19.8
160	0	1,929	16,880	16.5
180	0	1,729	16,880	15.1
200	0	1,612	16,880	14.9
220	0	1,579	16,880	15.4
240	0	1,547	16,880	14.1
260	0	1,560	16,880	13.7
280	0	1,621	16,880	14.6
300	0	1,681	16,880	11.8
320	0	1,637	12,333	14.2
340	0	1,490	12,333	13.7
360	0	1,343	12,333	11.6
380	0	1,196	12,333	11.3



## **APPENDIX C REPORT LIMITATIONS AND GUIDELINES FOR USE**

This appendix provides information to help you manage your risks with respect to the use of this report.

### **Report Use and Reliance**

The data report has been prepared for the Spokane Public Facilities District. The report is not intended for use by others, and the information contained herein is not applicable to other projects or properties. No party or parties other than those named above may rely on the product of our services unless we agree to such reliance in advance and in writing. The purpose of this limitation is to provide our firm with reasonable protection against open-ended liability claims by third parties with whom there would otherwise be no contractual limits to their actions.

This report is intended to be used only for the specific purpose or project originally contemplated for our services, and use of this report is not recommended for any other purpose or project. The data was developed and compiled for this project only, and no representation or warranty is made, either express or implied. GeoEngineers shall not be responsible for any alterations, modifications or additions to the data herein or the consequences of any interpretations of the data. Any use of the data, including any conclusion or information obtained or derived from the use of the data, other than by the Spokane Public Facilities District, their authorized agents and regulatory agencies for the specific purpose or project originally contemplated for our services will be at the user's sole risk.

If changes are made to the project or property after the date of the report, we recommend that GeoEngineers be given the opportunity to review the data, and then we can provide written modifications or confirmation, as appropriate.

### **Information Provided by Others**

GeoEngineers makes no warranties or guarantees regarding the accuracy or completeness of data provided or compiled by others and shall not be responsible for user's interpretation of such data.

Have we delivered World Class Client Service?  
Please let us know by visiting [www. geoengineers.com/feedback](http://www.geoengineers.com/feedback).

